KLIMAS Sp. z o.o. ul. W. Witosa 135/137 Kuźnica Kiedrzyńska 42-233 Mykanów tel. +48 34 377 71 00, fax. +48 34 328 01 73 Infolinia: 801 477 477, www.wkret-met.com.pl


Wkręt-met

PRODUCT DATA SHEET - TSM

Section 1. PRODUCT DESCRIPTION

METAL MESH SLEEVE - TSM

Metal mesh sleeve TSM is used for installation in hollow base materials. Mesh sleeve ensures uniform distribution and controlled application of resin (prevents resin from flowing out from between hollow base materials). Mesh sleeve is 100 cm long, allowing for flexible installation at any depth. The only thing required is to cut the mesh sleeve to an appropriate length and close its end to prevent the resin from flowing out.



Section 2. TECHNICAL DATA

TABLE 1. SELECTION TABLE			
Product code	Dimensions	Inner diameter	Number of pieces in a box
[-]	d _k x L _k [mm]	d _w [mm]	[-]
TSM-12	12 x 1000	8	1
TSM-16	16 x 1000	10 - 12	1
TSM-22	22 x 1000	16	1
TSM-26	26 x 1000	20	1

Section 3. REMARKS

- All previous versions of this Product Data Sheet shall cease to be valid
- Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.