

#### KLIMAS Sp. z o.o. ul. W. Witosa 135/137 Kuźnica Kiedrzyńska 42-233 Mykanów tel. +48 34 377 71 00, fax. +48 34 328 01 73 Infolinia: 801 477 477, www.wkret-met.com.pl




# **PRODUCT DATA SHEET - TSN**

# **Section 1. PRODUCT DESCRIPTION**

### NYLON MESH SLEEVE FOR FASTENING IN HOLLOW BASE MATERIALS - TSN

Nylon mesh sleeve TSN is used for installation in hollow base materials. Nylon mesh sleeve ensures uniform distribution and controlled application of resin (prevents resin from flowing out from between hollow base materials). The plug with a hole ensures easy alignment in the sleeve and prevents resin from flowing out. The mesh sleeve is made from nylon which is durable, flexible and has high fire resistance. Intended for standard installations at a depth of up to 130 mm.



# **Section 2. TECHNICAL DATA**

TABLE 1. SELECTION TABLE			
Product code	Dimensions	Inner diameter	Number of pieces in a box
[-]	d <sub>k</sub> x L <sub>k</sub> [mm]	d <sub>w</sub> [mm]	[-]
TSN-01	12 x 80	6-8	50
TSN-02	16 x 85	10-12	20
TSN-03	16 x 130	10-12	20
TSN-04	20 x 85	14-16	20

# **Section 3. REMARKS**

- 1. All previous versions of this Product Data Sheet shall cease to be valid
- 2. Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.