

PRODUCT DATA SHEET – WF-5,5


Section 1. PRODUCT DESCRIPTION

SELF-DRILLING SCREW WITH EPDM WASHER FOR FIXING STEEL SHEETS IN STEEL CONSTRUCTION – WF-5,5

Self-drilling screw WF-5,5 is made of heat-treated carbon steel in galvanized zinc coating 12 µm (WF/WFOC) or SQ Ceramic coating (WF-D). Screw has SW hex head, pin threaded for use in steel, self-drilling tip and EPDM washer. Self-drilling screw heads can be painted according to RAL palette providing coating which is resistant to mechanical damages and UV radiation and ensures permanent colour adjusted to roof covering.

Use:


- fixing steel sheets in steel constructions
- for mounting profiled sheets to steel structures



Self-drilling screws hold European Technical Assessment: ETA-16/0443


Section 2. METHOD OF INSTALLATION

1. Original self-drilling screws delivered by the manufacturer can be used only
2. Before installation identify the substrate, its thickness and environmental conditions (expressed as corrosivity categories), and then select screws which meet the above criteria
3. Correctly select screw type, its length, drilling capacity depending on sum of thickness values of members being fixed
4. Drilling capacity for each screw is given in corresponding Product Data Sheet and European Technical Assessment and stands for the sum of thickness values of members being fixed
5. Make sure to set optimum rotary speed when screwing (max. 1800 rpm), as too high rotary speed may cause burning of drilling bits and make it impossible to fasten the screw
6. At all times screws should be installed perpendicularly to the substrate surface
7. Make sure to press the washer correctly, as when the washer is pressed either too strongly or too weakly, lack of tightness is likely, which may result in corrosion in the fixing point



PRODUCT DATA SHEET – WF-5,5

Section 3. TECHNICAL DATA



TECHNICAL PARAMETERS		
Parameter	Unit	Value
Screw diameter	d_w [mm]	5,5
Drilling capacity	Σt [mm]	≤ 5
Wrench size	S [mm]	SW-8
Head height	k [mm]	4,9
Head diameter	F [mm]	10,5
Tip length	[mm]	9,0
Screw material	-	carbon steel
Corrosion protection	WFOC/WF	galvanized zinc coating 12 μ m
	WF-D	SQ Ceramic coating
EPDM washer D [mm]	WFOC/WF	steel Z16
	WF-D	aluminium A16
Coating to RAL palette	-	min. 60 μ m
Substrate material	-	steel \geq S280GD
European Technical Assessment	-	ETA-16/0443

INSTALLATION PARAMETERS		
Parameter	Unit	Value
Screw diameter	d_w [mm]	5,5
Diameter of hole in the substrate	d_o [mm]	-
Min. depth of hole in the substrate	h_o [mm]	-
Anchorage depth	h_{eff} [mm]	push-through
Min. substrate thickness	h_{min} [mm]	1,0
Min. spacing	s_{min} [mm]	50
Min. distance from edge	c_{min} [mm]	25

RESISTANCE						
Characteristic pull-out / shear strength [kN]						
Substrate thickness [mm]	Steel sheet thickness [mm]					
	0,50	0,63	0,75	0,88	1,00	1,25 ÷ 2,00
1,00	1,10/1,53	1,10/1,88	1,10/2,52	1,10/2,87	1,10/2,90	1,10/4,09
1,25	1,86/1,53	1,86/1,88	1,86/2,52	1,86/2,87	1,86/2,90	1,86/4,09
1,50	1,97/1,53	1,97/1,88	1,97/2,52	1,97/2,87	1,97/2,90	1,97/4,09
2,00 ÷ 3,00	2,99/1,53	2,99/1,88	2,99/2,52	2,99/2,87	2,99/2,90	2,99/4,09

*Partial safety factor of 1.33 recommended

SELECTION TABLE						
WFOC (galvanized zinc coating ZN)	WF* (galvanized zinc coating ZN + RAL)	WF-D* (SQ Ceramic coating)	WF-D-RAL* (SQ Ceramic coating + RAL)	Screw dimensions	Max. usable length	Number of pieces in a box
				$d_w \times L_w$ [mm]	t_{fix} [mm]	[pcs]
WFOC-55019-Z16	WF-55019-Z16-RAL	WF-D-55019-A16	WF-D-55019-A16-RAL	5,5 x 19	1	250
WFOC-55025-Z16	WF-55025-Z16-RAL	WF-D-55025-A16	WF-D-55025-A16-RAL	5,5 x 25	7	250
WFOC-55032-Z16	WF-55032-Z16-RAL	WF-D-55032-A16	WF-D-55032-A16-RAL	5,5 x 32	14	250
WFOC-55038-Z16	WF-55038-Z16-RAL	WF-D-55038-A16	WF-D-55038-A16-RAL	5,5 x 38	20	250
WFOC-55045-Z16	WF-55045-Z16-RAL	WF-D-55045-A16	WF-D-55045-A16-RAL	5,5 x 45	27	250
WFOC-55050-Z16	WF-55050-Z16-RAL	WF-D-55050-A16	WF-D-55050-A16-RAL	5,5 x 50	32	100
WFOC-55060-Z16	WF-55060-Z16-RAL	WF-D-55060-A16	WF-D-55060-A16-RAL	5,5 x 60	42	100
WFOC-55075-Z16	WF-55075-Z16-RAL	WF-D-55075-A16	WF-D-55075-A16-RAL	5,5 x 75	57	100

*Screw on request and to order

PRODUCT DATA SHEET – WF-5,5

Section 4. REMARKS

1. All previous versions of this Product Data Sheet shall cease to be valid
2. Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.