

PRODUCT DATA SHEET – TFIB-X

Section 1. PRODUCT DESCRIPTION

HIGHLY ADHESIVE FIBREGLASS TAPE – TFIB-X

Highly adhesive fibreglass tape TFIB-X is used for reinforcing plasterboard joints, covering small cracks and repairing major cracks in plaster or repairing damages of plasterboard framing. The tape features excellent adherence to plasterboards compared with the classic tape. It is perfect for environments with increased humidity (provides excellent adherence with humidity of up to 90%.) Suitable for use in temperature range of 5°C to 35°C.



Section 2. METHOD OF INSTALLATION

1. Before application of the tape clean surface of the boards
2. Apply adhesive tape on plasterboard joint
3. Once plasterboards are joined with tape apply thin layer of joint compound on the tape
4. After the compound has dried, apply consequent wider layer until the mesh is immersed completely
5. After all layers are applied, smooth out the compound to achieve uniform and smooth surface

Section 3. TECHNICAL DATA

SELECTION TABLE		
Product code	Size (width x length)	Number of pieces in a box
TFIB-04890-X	48 mm x 90 lm	12

Section 4. REMARKS

1. All previous versions of this Product Data Sheet shall cease to be valid
2. Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.